

Balzer



Balzer marka ürünler Özhat tarafından Türkiye'ye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir Balzer ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırılacaktır

Balzer Ürün Listesi

Ürün	Tarif
BN 809 801	Insulating Bushes (For Cross beam Ion source)
BPU -431	Üst Dereceli Kontrol Sistemi, Vakum Kaplama Makinesi
312ZRA160	Merkezleme halkası ile dış halka
DIFFUSION PUMP 160 ISO. BALZER BP D060 000 OR EQUIVALENT	High Vacuum Connection DN 160 ISO-K Fore Vacuum Connection DN 40 KF Pumping speed of Diffusion Pump 1100 I/S With Baffle BFA...W/L 620 I/S With Baffle BFA...W/L 580 I/S With BFA...M/MF and Plate Valve 425 I/S For Water vapor with LN2 cooling 2700 3-phase 380v/50Hz
DUO 35. ROTARY VANE PUMP 230/400 V. 50 HZ. 3TF 265/460 V.60 HZ FOR LUBRICANT P3 CATALOG # PK D45 602	Nominal Volume Flow rate at 50 ~ 38m3/h Volume flow rate at 50 Hz, ~ 34m3/h Ultimate Pressure Partial, without gas ballast <1x10-4mbar Total, without gas ballast <2x10-3mbar Partial, with gas ballast <1 x 10-3 mbar Total, with gas ballast <2 x 10-3 mbar
HENA 40. ROTARY VANE PUMP 109- 208/380-415 V. 50 HZ. 3TF 220- 230/440-460 V. 60 HZ OPERATING MEDIUM P3	Nominal Volume Flow rate at 50 Hz, ~ 38m3/h Volume flow rate at 50 Hz, ~ 34m3/h Ultimate Pressure Partial, without gas ballast <2x10-2mbar Total, without gas ballast <3x10-2mbar Partial, with gas ballast <1 mbar Total, with gas ballast <1 mbar
IKR 251. ACTIVE COLD CATHODE TRANSMITTER DN 40 ISO-KF CATALOG # PT R25 501	-Measurement range: 2 x E-9 to 1 x E-2 mbar -Bakeout temperature: 150°C (302°F) with electronics removed -Accuracy: +/- 30% (From 1 x E-8 to 1 x E-3 mbar) -Reproducibility: +/- 5% (From 1 x E-8 to 1 x E-3 mbar) -Signal Output: 0 - 10.5V -Supply Voltage: 15 - 30VDC -FPM sealed
MULTI POCKET ROTATABLE ELECTRON BEAM SOURCE WITH MANUALLY OPERATED POWER SUPPLY DEFLECTION 270 DEG	Pockets 04 (15 cc each) Water cooled Power supply Power rating ~6KW High voltage range -6KV to -10KV XY position movement 10 mm Working pressure ~ 7 x 10-4 to 1 x 10-6 m bar
SALES PROMOTION TURBO HIPACE 400 PACKAGE DN 100 ISO- KCATALOG # PM 153 921 -T	HiPace 400; DN 100 ISO-K; TC 400; DCU 400; mains cable; connection cable; air cooling; USB stick (software TurboViewer)
TPG 256 A	- Measurement Units: mbar, Torr, Pa - Interface: RS232C, RS422 - Analog Output: 0 – 10VDC - Switching Functions: 6
VAX 3100/40 (MODEL 450ZM-B9)	Computer,DIGITAL with control program of BPU 431 Blazers Coating Machine (BAK-760) Re-furbished)
TPR 010	Pirani ölçüm tüpü
PT 120 302 -T	PKR 360, PKR 361 için, bölmeyi Ölçüm

Ürün	Tarif
PT 120 300 -T	bölme cpl ölçülmesi. İR '360/361 ve ICT 011
BN845995-T	IR ateşleme cihazı 10